

## DECLARATION OF PERFORMANCE

**CONF-DOP\_BA-08-22**

No. H03-13/0401

1.	Unique identification code of the product-type	<b>DEMU Bolt anchor and Plate anchor</b>
2.	Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	<b>DEMU Bolt anchor, type 1988</b> - See ETA-13/0401, Annexes A6, A7 and A8; <b>DEMU Bolt anchor, type 1985</b> - See ETA-13/0401, Annexes A6, A7 and A8; <b>DEMU Plate anchor, type 1980-P</b> - See ETA-13/0401, Annexes A6, A7 and A8
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	
	Generic type and use	Cast-in fixing anchor with internal threaded socket
	Product size covered	M12×55, M12×100, M12×150, M16×75, M16×140, M16×220, M20×90, M20×150, M20×180, M20×270, M24×110, M24×200, M24×320, M30×160, M30×240, M30×380, M36×300, M36×420, M42×300, M42×460
	For use in	Cracked and non-cracked concrete C20/25 to C90/105 according EN 206:2013+A1:2016
	Base material / base material strength	<ul style="list-style-type: none"> <li>• Sleeve in electroplated steel for dry internal conditions, insignificant corrosion exposure</li> <li>• Sleeve in hot-dipped galvanised steel for low corrosion exposure</li> <li>• Sleeve in stainless steel (A4-50 and A4-80) for medium corrosion exposure</li> <li>• Sleeve and bolt in stainless steel (A4-80) for strong and very strong corrosion exposure</li> </ul>
	Loading	Static & quasi static tension and shear loads or the combination of tension and shear loads
4.	Name, registered trade name or registered trademark and contact address of the manufacturer as required pursuant to Article 11(5)	Leviat GmbH, Liebigstraße 14, 40764 Langenfeld, Germany
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	-
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 1
7.	In case of the declaration of performance concerning a construction product covered by a harmonised standard	-
8.	In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	<p>Deutsches Institut für Bautechnik (DIBt) issued ETA-13/0401 on the basis of EAD 330012-00-0601, the notified body 2323 performed under system 1</p> <p>(i) Determination of the product type on the basis of type testing (including sample-testing), type calculation, tabulated values or descriptive documentation of the product;</p> <p>(ii) Initial inspection of the manufacturing plant and of factory production control;</p> <p>(iii) Continuous surveillance, assessment and evaluation of</p>

## DECLARATION OF PERFORMANCE

**CONF-DOP\_BA-08-22**

No. H03-13/0401

		factory production control and issued certificate 2323-CPR-0013.		
	Declared performance			
	Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
9.	Characteristic resistance for tension	EN 1992-4-1 and EN 1992-4-2	ETA-13/0401, Annexes C1 and C2	EAD 330012-00-0601
	Characteristic resistance for shear		ETA-13/0401, Annexes C3 and C4	
	Displacement for serviceability limit state		ETA-13/0401, Annexes C2 and C4	
	Characteristic resistance for fire		ETA-13/0401, Annex C5	
	Where pursuant to Article 37 or 38 in the Specific Technical Documentation has been used, the requirements with which the product complies		-	
10.	The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.			
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.				

Langenfeld, 04.08.2022

Signed for and on behalf of the manufacturer by



Chris Oberli  
(Managing Director | Europe Central)



Dr. Ing. Dirk Albartus  
(Prokurist))

# DECLARATION OF PERFORMANCE

CONF-DOP\_BA-08-22

No. H03-13/0401

Page 19 of European Technical Assessment  
ETA-13/0401 of 23 June 2022

English translation prepared by DIBt



Table C1a: Characteristic values for tension loads

Thread size	d	[mm]	M12	M16	M20	M24	M30	M36	M42	
<b>Steel failure, bolt / plate anchor (material 1 or 2) and screw (min. steel strength 4.6) made of electroplated / hot-dipped galvanised steel</b>										
Characteristic resistance	$N_{Rk,s}$	[kN]	33,7	62,8	98,0	141,2	224,4	326,8	448,4 <sup>2)</sup>	
Partial factor	$\gamma_{Ms}$ <sup>1)</sup>	[-]	2,00							
<b>Steel failure, bolt / plate anchor (material 1 or 2) and screw (min. steel strength 5.6) made of electroplated / hot-dipped galvanised steel</b>										
Characteristic resistance	$N_{Rk,s}$	[kN]	42,2	78,5	122,5	176,5	280,5	408,5	560,5 <sup>2)</sup>	
Partial factor	$\gamma_{Ms}$ <sup>1)</sup>	[-]	2,00							
<b>Steel failure, bolt / plate anchor (material 1 or 2) and screw (min. steel strength 8.8) made of electroplated / hot-dipped galvanised steel</b>										
Characteristic resistance	$N_{Rk,s}$	[kN]	45,8	93,1	139,6	219,5	335,0	490,5	588,1 <sup>2)</sup>	
Partial factor	$\gamma_{Ms}$ <sup>1)</sup>	[-]	1,58							
<b>Steel failure, bolt anchor (material 3: A4-50) and screw (min. steel strength A4-50) made of stainless steel</b>										
Characteristic resistance	$N_{Rk,s}$	[kN]	42,2	81,0	110,3	4)				
Partial factor	$\gamma_{Ms}$ <sup>1)</sup>	[-]	2,86	3,09	4)					
<b>Steel failure, bolt anchor (material 3: A4-50) and screw (min. steel strength A4-70) made of stainless steel</b>										
Characteristic resistance	$N_{Rk,s}$	[kN]	46,4	81,0	110,3	4)				
Partial factor	$\gamma_{Ms}$ <sup>1)</sup>	[-]	3,09							
<b>Steel failure, bolt / plate anchor (material 4: A4-80) and screw (min. steel strength A4-80) made of stainless steel</b>										
Characteristic resistance	$N_{Rk,s}$	[kN]	59,0	125,6	180,1	282,4	448,8	4)		
Partial factor	$\gamma_{Ms}$ <sup>1)</sup>	[-]	1,48	1,60	1,48	1,60		4)		
<b>Pull-out failure</b>										
Characteristic resistance in cracked concrete	C20/25	$N_{Rk,p}$	[kN]	25,1	44,7	69,8	100,5	168,9	240,3	341,0
				218,5 <sup>3)</sup>	338,9 <sup>3)</sup>	483 <sup>3)</sup>	880,4 <sup>3)</sup>	1225,5 <sup>3)</sup>	4)	
Characteristic resistance in uncracked concrete	C20/25	$N_{Rk,p}$	[kN]	35,2	62,5	97,7	140,7	236,4	336,4	477,4
				305,9 <sup>3)</sup>	474,5 <sup>3)</sup>	676,2 <sup>3)</sup>	1232,5 <sup>3)</sup>	1715,6 <sup>3)</sup>	4)	
Increasing factors for $N_{Rk,p} = N_{Rk,p(C20/25)} \cdot \Psi_C$ in cracked and uncracked concrete	C25/30	$\Psi_C$	[-]	1,25						
	C30/37	$\Psi_C$	[-]	1,50						
	C35/45	$\Psi_C$	[-]	1,75						
	C40/50	$\Psi_C$	[-]	2,00						
	C45/55	$\Psi_C$	[-]	2,25						
Partial factor	C50/60	$\Psi_C$	[-]	2,50						
	$\gamma_{Mp}$ <sup>1)</sup>	[-]	1,50							

<sup>1)</sup> in absence of other national regulations

<sup>2)</sup> only available in GV (material 1 according to Annex A7)

<sup>3)</sup> only valid for plate anchor 1980-P

<sup>4)</sup> no performance assessed

DEMU Bolt anchor and Plate anchor

Performances  
Characteristic values for tension loads

Annex C1

Z125208.21

8.06.01-32/19

# DECLARATION OF PERFORMANCE

CONF-DOP\_BA-08-22

No. H03-13/0401

Page 20 of European Technical Assessment  
ETA-13/0401 of 23 June 2022

English translation prepared by DIBt



Table C1b: Characteristic values for tension loads in cracked and uncracked concrete

Thread size	d	[mm]	M12	M16	M20	M24	M30	M36	M42
Effective anchorage depth	$h_{ef}^{1)}$	[mm]	x55:	x75:	x90:	x110:	x160:	x300:	x300:
			49,0	67,0	79,0	97,0	143,0	279,0	276,0
			x100:	x140:	x150:	x200:	x240:	x420:	x460:
			94,0	132,0	139,0	187,0	223,0	399,0	436,0
			x150:	x220:	x180:	x320:	x380:		
144,0	212,0	169,0	307,0	363,0					
			x270:						
			259,0						
			$x \geq 55:$	$x \geq 75:$	$x \geq 90:$	$x \geq 110:$	$x \geq 160:$	$x \geq 300:$	$x \geq 300:$
			$h_{ef}^{2)}$	$h_{ef}^{2)}$	$h_{ef}^{3)}$	$h_{ef}^{3)}$	$h_{ef}^{3)}$	$h_{ef}^{3)}$	$h_{ef}^{3)}$
<b>Concrete cone failure</b>									
Factor to take into account the influence of load transfer mechanisms	$k_1$	[-]	8,9						
		[-]	12,7						
Characteristic Resistance	$N_{Rk,sp}^0$	[mm]	$N_{Rk,sp}^0 = \min \{N_{Rk,c}^0; N_{Rk,p}^0\}^{4)}$						
Characteristic spacing	$s_{Cr,N}$	[mm]	$3,0 \cdot h_{ef}$						
Characteristic edge distance	$c_{Cr,N}$	[mm]	$1,5 \cdot h_{ef}$						
Partial factor	$\gamma_{Mc}^{2)}$	[-]	1,50						
<b>Splitting</b>									
Characteristic spacing	$s_{Cr,sp}$	[mm]	$3,0 \cdot h_{ef}$						
Characteristic edge distance	$c_{Cr,sp}$	[mm]	$1,5 \cdot h_{ef}$						
Partial factor	$\gamma_{Msp}^{2)}$	[-]	1,50						

<sup>1)</sup> for bolt anchor type 1985 the values have to be decreased by 2,0 mm, for plate anchor type 1980-P the values have to be decreased by the plate thickness m

<sup>2)</sup> in absence of other national regulations

<sup>3)</sup>  $h_{ef} = L - k + 2$  [mm] for bolt anchor type 1988,  $h_{ef} = L - k$  [mm] for bolt anchor type 1985,  $h_{ef} = L - k - m + 2$  [mm] for plate anchor type 1980-P, m in accordance with Annex A5 Table A4

<sup>4)</sup>  $N_{Rk,c}^0$  according to EN 1992-4:2018

Table C2: Displacements under tension loads in cracked and uncracked concrete

Thread size	d	[mm]	M12	M16	M20	M24	M30	M36	M42
Displacements $\delta_{N0}$ to 0.7 mm for short term loading under following tension loads <sup>1)</sup>	N	[kN]	14,0	20,0	29,0	40,0	63,0	83,0	113,0

<sup>1)</sup> for long term tension loading the displacements  $\delta_{N\infty}$  can be increased to 1,8 mm

DEMU Bolt anchor and Plate anchor

Performances  
Characteristic values for tension loads, displacements under tension loads

Annex C2

# DECLARATION OF PERFORMANCE

**CONF-DOP\_BA-08-22**

No. H03-13/0401

Page 21 of European Technical Assessment  
ETA-13/0401 of 23 June 2022

English translation prepared by DIBt



Table C3a: Characteristic values for shear loads									
Thread size	d	[mm]	M12	M16	M20	M24	M30	M36	M42
<b>Shear loads without lever arm</b>									
Group factor (EN 1992-4:2019, 7.2.2.3.1)	$k_7$	[-]	1,0						
<b>Steel failure, bolt anchor (material 1 or 2) and screw (min. steel strength 4.6) made of electroplated / hot-dipped galvanised steel</b>									
Characteristic resistance	$V_{Rk,s}$	[kN]	16,9	31,4	49,0	70,6	112,2	163,4	224,2 <sup>2)</sup>
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,67						
<b>Steel failure, bolt anchor (material 1 or 2) and screw (min. steel strength 5.6) made of electroplated / hot-dipped galvanised steel</b>									
Characteristic resistance	$V_{Rk,s}$	[kN]	21,1	39,3	61,3	88,3	140,3	204,3	280,3 <sup>2)</sup>
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,67						
<b>Steel failure, bolt anchor (material 1 or 2) and screw (min. steel strength 8.8) made of electroplated / hot-dipped galvanised steel</b>									
Characteristic resistance	$V_{Rk,s}$	[kN]	22,9	46,5	69,8	109,7	167,5	245,2	294,1 <sup>2)</sup>
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,32						
<b>Steel failure, bolt anchor (material 3: A4-50) and screw (min. steel strength A4-50) made of stainless steel</b>									
Characteristic resistance	$V_{Rk,s}$	[kN]	21,1	40,5	55,1	3)			
Partial factor	$\gamma_{Ms}^{1)}$	[-]	2,38	2,58	3)				
<b>Steel failure, bolt anchor (material 3: A4-50) and screw (min. steel strength A4-70) made of stainless steel</b>									
Characteristic resistance	$V_{Rk,s}$	[kN]	23,2	40,5	55,1	3)			
Partial factor	$\gamma_{Ms}^{1)}$	[-]	2,58						
<b>Steel failure, bolt anchor (material 4: A4-80) and screw (min. steel strength A4-80) made of stainless steel</b>									
Characteristic resistance	$V_{Rk,s}$	[kN]	29,5	62,8	90,0	141,2	224,4	3)	
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,23	1,33	1,23	1,33	3)		
<b>Shear loads with lever arm: see Annex C4, Table C3b</b>									
<b>Pry-out failure</b>			<b>M12</b>	<b>M16</b>	<b>M20</b>	<b>M24</b>	<b>M30</b>	<b>M36</b>	<b>M42</b>
Factor	$k_8$	[-]	x55: 1,0 x100: 2,0 x150: 2,0	2,0	2,0	2,0	2,0	2,0	2,0
Partial factor	$\gamma_{Mcp}^{1)}$	[-]	1,50						
<b>Concrete edge failure (without suppl. reinforcement)</b>			<b>M12</b>	<b>M16</b>	<b>M20</b>	<b>M24</b>	<b>M30</b>	<b>M36</b>	<b>M42</b>
Effective length of fixing anchor (for shear loads)	$l_f$	[mm]	x55: 49,0	x75: 67,0	x90: 79,0	x110: 97,0	x160: 143,0	x300: 279,0	x300: 276,0
			x100: 94,0	x140: 132,0	x150: 139,0	x200: 187,0	x240: 223,0	x420: 380,0	x460: 432,0
Effective outside diameter	$d_{nom}$	[mm]	x150: 144,0	x220: 212,0	x180: 169,0	x320: 307,0	x380: 320,0		
					x270: 259,0				
			x ≥55: $h_{ef}$	x ≥75: $h_{ef}$	x ≥90: $h_{ef}$	x ≥110: $h_{ef}$	x ≥160: $h_{ef}$	x ≥300: $h_{ef}$	x ≥300: $h_{ef}$
Partial factor	$\gamma_{Mce}^{1)}$	[-]	1,50						
<sup>1)</sup> in absence of other national regulations <sup>2)</sup> only available in GV (material 1 according to Annex A7) <sup>3)</sup> no performance assessed									
DEMU Bolt anchor and Plate anchor								Annex C3	
Performances Characteristic values for shear loads									

Z125208.21

8.06.01-32/19

# DECLARATION OF PERFORMANCE

**CONF-DOP\_BA-08-22**

No. H03-13/0401

Page 22 of European Technical Assessment  
ETA-13/0401 of 23 June 2022

English translation prepared by DIBt



Table C3b: Characteristic values for shear loads

Thread size	d	[mm]	M12	M16	M20	M24	M30	M36	M42
<b>Shear loads with lever arm</b>									
<b>Steel failure, bolt / plate anchor (material 1 or 2) and screw (min. steel strength 4.6) made of electroplated / hot-dipped galvanised steel</b>									
Characteristic resistance	$M_{Rk,s}^0$	[Nm]	52,4	133,2	259,6	449,0	899,6	1581,0	2541,1 <sup>2)</sup>
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,67						
<b>Steel failure, bolt / plate anchor (material 1 or 2) and screw (min. steel strength 5.6) made of electroplated / hot-dipped galvanised steel</b>									
Characteristic resistance	$M_{Rk,s}^0$	[Nm]	65,5	166,5	324,5	561,3	1124,5	1976,3	3176,3 <sup>2)</sup>
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,67						
<b>Steel failure, bolt / plate anchor (material 1 or 2) and screw (min. steel strength 8.8) made of electroplated / hot-dipped galvanised steel</b>									
Characteristic resistance	$M_{Rk,s}^0$	[Nm]	104,8	266,4	519,3	898,0	1799,2	3162,1	5082,1 <sup>2)</sup>
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,25						
<b>Steel failure, bolt anchor (material 3: A4-50) and screw (min. steel strength A4-50) made of stainless steel</b>									
Characteristic resistance	$M_{Rk,s}^0$	[Nm]	65,5	166,5	324,5	3)			
Partial factor	$\gamma_{Ms}^{1)}$	[-]	2,38						
<b>Steel failure, bolt anchor (material 3: A4-50) and screw (min. steel strength A4-70) made of stainless steel</b>									
Characteristic resistance	$M_{Rk,s}^0$	[Nm]	91,7	383,7	659,4	3)			
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,56	2,58					
<b>Steel failure, bolt anchor (material 3: A4-50) and screw (min. steel strength A4-80) made of stainless steel</b>									
Characteristic resistance	$M_{Rk,s}^0$	[Nm]	161,6	383,7	659,4	3)			
Partial factor	$\gamma_{Ms}^{1)}$	[-]	2,58						
<b>Steel failure, bolt / plate anchor (material 4: A4-80) and screw (min. steel strength A4-80) made of stainless steel</b>									
Characteristic resistance	$M_{Rk,s}^0$	[Nm]	104,8	266,4	519,3	898,0	1799,2	3)	
Partial factor	$\gamma_{Ms}^{1)}$	[-]	1,33						

<sup>1)</sup> in absence of other national regulations

<sup>2)</sup> only available in GV (material 1 according to Annex A7)

<sup>3)</sup> No performance assessed

Table C4: Displacements under shear loads in cracked and uncracked concrete

Thread size	d	[mm]	M12	M16	M20	M24	M30	M36	M42
Displacements $\delta_{v0}$ to 1.5 mm for short term loading under following shear loads <sup>1)</sup>	V	[kN]	13,0	23,0	36,0	52,0	82,0	120,0	160,0

<sup>1)</sup> for long term shear loading the displacements  $\delta_{v+}$  can be increased to 2,0 mm

DEMU Bolt anchor and Plate anchor

Performances  
Characteristic values for shear loads, displacements under shear loads

Annex C4

# DECLARATION OF PERFORMANCE

**CONF-DOP\_BA-08-22**

No. H03-13/0401

Page 23 of European Technical Assessment  
ETA-13/0401 of 23 June 2022

English translation prepared by DIBt



Table C5: Characteristic values for resistance to fire

Thread size	d	[mm]	M12	M16	M20	M24	M30	M36	M42
<b>Steel failure for tension and shear load (<math>F_{Rk,s,fi} = N_{Rk,s,fi} = V_{Rk,s,fi}</math>), bolt anchor (material 1 or 2) and screw made of electroplated / hot-dipped galvanised steel</b>									
Characteristic resistance	R30	$F_{Rk,s,fi}$ [kN]	1,5	3,0	4,5	7,1	10,8	15,8	19,0
	R60	$F_{Rk,s,fi}$ [kN]	1,1	2,3	3,4	5,3	8,1	11,9	14,2
	R90	$F_{Rk,s,fi}$ [kN]	1,0	2,0	2,9	4,6	7,0	10,3	12,3
	R120	$F_{Rk,s,fi}$ [kN]	0,7	1,5	2,3	3,5	5,4	7,9	9,5
Partial factor	$\gamma_{Ms,fi}^{(1)}$	[-]	1,00						
Characteristic resistance	R30	$M^0_{Rk,s,fi}$ [Nm]	2,6	6,7	13,0	22,5	45,0	79,1	127,1
	R60	$M^0_{Rk,s,fi}$ [Nm]	2,0	5,0	9,7	16,8	33,7	59,3	95,3
	R90	$M^0_{Rk,s,fi}$ [Nm]	1,7	4,3	8,4	14,6	29,2	51,4	82,6
	R120	$M^0_{Rk,s,fi}$ [Nm]	1,3	3,3	6,5	11,2	22,5	39,5	63,5
Partial factor	$\gamma_{Ms,fi}^{(1)}$	[-]	1,00						
<b>Steel failure for tension and shear load (<math>F_{Rk,s,fi} = N_{Rk,s,fi} = V_{Rk,s,fi}</math>), bolt anchor (material 3 or 4) and screw made of stainless steel</b>									
Characteristic resistance	R30	$F_{Rk,s,fi}$ [kN]	2,2 / 2,5 <sup>2)</sup>	4,5 / 4,6 <sup>2)</sup>	6,8	10,6	16,2	3)	3)
	R60	$F_{Rk,s,fi}$ [kN]	1,8 / 2,1 <sup>2)</sup>	3,8 / 3,9 <sup>2)</sup>	5,6	8,8	13,5		
	R90	$F_{Rk,s,fi}$ [kN]	1,5 / 1,6 <sup>2)</sup>	3,0 / 3,1 <sup>2)</sup>	4,5	7,1	10,8		
	R120	$F_{Rk,s,fi}$ [kN]	1,2 / 1,3 <sup>2)</sup>	2,4 / 2,5 <sup>2)</sup>	3,6	5,6	8,6		
Partial factor	$\gamma_{Ms,fi}^{(1)}$	[-]	1,00						
Characteristic resistance	R30	$M^0_{Rk,s,fi}$ [Nm]	3,9	10,0	19,5	33,7	67,5	3)	3)
	R60	$M^0_{Rk,s,fi}$ [Nm]	3,3	8,3	16,2	28,1	56,2		
	R90	$M^0_{Rk,s,fi}$ [Nm]	2,6	6,7	13,0	22,5	45,0		
	R120	$M^0_{Rk,s,fi}$ [Nm]	2,1	5,3	10,4	18,0	36,0		
Partial factor	$\gamma_{Ms,fi}^{(1)}$	[-]	1,00						
<b>Pull-out failure</b>									
Characteristic resistance	R90	$N_{Rk,p,fi}$ [kN]	$N_{Rk,p,fi(90)} = 0,25 \cdot N_{Rk,p}$						
	R120	$N_{Rk,p,fi}$ [kN]	$N_{Rk,p,fi(120)} = 0,20 \cdot N_{Rk,p}$						
Partial factor	$\gamma_{Mp,fi}^{(1)}$	[-]	1,00						

<sup>1)</sup> in absence of other national regulations

<sup>2)</sup> higher value applies for material 3 (according to Annex A7)

<sup>3)</sup> no performance assessed

DEMU Bolt anchor and Plate anchor

Performances  
Characteristic values for resistance to fire

Annex C5

Z125208.21

8.06.01-32/19